PRODUCT FICHE

körting



ょ

ぇ

\$55

ゃ

*0

0/11/

FC6A3A-MSAA2 - KE6141BRM 729336

Electric cooker

USP :

SilverMatte

Surface door temperature

Door hinge Oven type

Maximum oven temperature Product group Knob shape Guiding of drawer 1

Double glazed oven door with one heat deflector (CompactDoor) Classic door hinge Multisystem oven BigSpace - 65 I SuperSize baking area 275 °C Cooker Ergonomic knobs Classic 1/2

Basic information :

Microwave function Product group Brand Commercial code Internal article number EAN code Main colour of the product Color / Material front Construction type Installation type Type of control Cooking method Total number of positions that can be used at the same time Number of gas burners Number of electric cooking zones Number of electric plates Number of radiant plates Number of halogenous plates Number of induction plates Number of electric warming zones Location of control panel Which kind of hobs can be controlled? Energy input Electric connection rating (W) Current (A) Voltage (V) Frequency (Hz) Marks of conformity Plug type Adjustable feet Height of the product (mm) Width of the product (mm) Depth of the product (mm) Height of the packed product (mm) Width of the packed product (mm) Depth of the packed product (mm) Net weight (kg) Gross weight (kg) Material of external sides

Features :

Electronic timer Short description of the product Painted Control panel material Oven guides Wire type 1x Grids 1 Mechanical Temperature control Time control Mechanical Time-setting options No delay option Oven pans 2

Electric cooker Korting FC6A3A-MSAA2 - KE6141BRM 729336 3838782066696 Black brown Black brown / Painted Free-standing Free-standing Mechanical Multisystem 4 / 4 / 4 / 4 / 4 / 4 / 2 Voker front Electric Electricty 8700 W / / 220-240 50/60 CE,VDEGS Without plug and supply cord Yes - all 850 mm 600 mm 600 mm 600 mm 600 mm 676 mm 719 mm 44,0 Kg 49,0 Kg	No
FC6A3A-MSAA2 - KE6141BRM 729336 3838782066696 Black brown Black brown / Painted Free-standing Free-standing Mechanical Multisystem 4 / 4 / 4 / 4 / / 4 / // </td <td>Electric cooker</td>	Electric cooker
729336 3838782066696 Black brown Black brown / Painted Free-standing Free-standing Mechanical Multisystem 4 / 4 / 4 / 4 / 4 / / 4 /	Korting
3838782066696 Black brown Black brown / Painted Free-standing Free-standing Mechanical Multisystem 4 / 4 / 4 / 4 / 4 / 4 / / 4 / <	FC6A3A-MSAA2 - KE6141BRM
Black brownPaintedFree-standingFree-standingMechanicalMultisystem4/4/4/4/// <tr< td=""><td>729336</td></tr<>	729336
Black brown / PaintedFree-standingFree-standingMechanicalMultisystem4/4/4// <td>3838782066696</td>	3838782066696
Free-standing Mechanical Multisystem 4 / 4 / 4 / <td>Black brown</td>	Black brown
Free-standing Mechanical Multisystem 4 / 4 / 4 / <td>Black brown / Painted</td>	Black brown / Painted
Mechanical Multisystem 4 / 4 4 / 4 /	Free-standing
Multisystem 4 / 4 4 /	•
4 / 4 4 4 / / / / 4 Cooker front Electric Electricity 8700 W / 220-240 50/60 CE,VDEGS Without plug and supply cord Yes - all 850 mm 600 mm 600 mm 600 mm 600 mm 960 mm 676 mm 719 mm 44,0 Kg 49,0 Kg	
/ 4 4 4 / / / / 4 Cooker front Electric Electric Electricity 8700 W / 220-240 50/60 CE,VDEGS Without plug and supply cord Yes - all 850 mm 600 mm 600 mm 600 mm 960 mm 676 mm 719 mm 44,0 Kg 49,0 Kg	•
4 4 / / / / 20-240 50/60 CE,VDEGS Without plug and supply cord Yes - all 850 mm 600 mm 600 mm 600 mm 600 mm 960 mm 676 mm 719 mm 44,0 Kg 49,0 Kg	•
4 / / 4 Cooker front Electric Electricity 8700 W / 220-240 50/60 CE,VDEGS Without plug and supply cord Yes - all 850 mm 600 mm 600 mm 600 mm 600 mm 960 mm 614 515 516 516 516 517 517 517 517 517 517 517 517	-
/ / / 4 Cooker front Electric Electricity 8700 W / 220-240 50/60 CE,VDEGS Without plug and supply cord Yes - all 850 mm 600 mm 600 mm 600 mm 600 mm 611 600 mm 600 mm 600 mm 600 mm	•
/ / 4 Cooker front Electric Electricity 8700 W / 220-240 50/60 CE,VDEGS Without plug and supply cord Yes - all 850 mm 600 mm 600 mm 600 mm 600 mm 616 mm 719 mm 44,0 Kg 49,0 Kg	-
/ 4 Cooker front Electric Electricity 8700 W / 220-240 50/60 CE,VDEGS Without plug and supply cord Yes - all 850 mm 600 mm 600 mm 600 mm 600 mm 960 mm 719 mm 44,0 Kg 49,0 Kg	
4 Cooker front Electric Electricity 8700 W / 220-240 50/60 CE,VDEGS Without plug and supply cord Yes - all 850 mm 600 mm 600 mm 600 mm 676 mm 719 mm 44,0 Kg 49,0 Kg	-
Cooker front Electric Electricity 8700 W / 220-240 50/60 CE,VDEGS Without plug and supply cord Yes - all 850 mm 600 mm 600 mm 600 mm 676 mm 719 mm 44,0 Kg 49,0 Kg	-
Electric Electricity 8700 W / 220-240 50/60 CE,VDEGS Without plug and supply cord Yes - all 850 mm 600 mm 600 mm 600 mm 676 mm 719 mm 44,0 Kg 49,0 Kg	•
Electricity 8700 W / 220-240 50/60 CE,VDEGS Without plug and supply cord Yes - all 850 mm 600 mm 600 mm 960 mm 676 mm 719 mm 44,0 Kg 49,0 Kg	
8700 W / 220-240 50/60 CE,VDEGS Without plug and supply cord Yes - all 850 mm 600 mm 600 mm 960 mm 676 mm 719 mm 44,0 Kg 49,0 Kg	
/ 220-240 50/60 CE,VDEGS Without plug and supply cord Yes - all 850 mm 600 mm 600 mm 960 mm 676 mm 719 mm 44,0 Kg 49,0 Kg	•
220-240 50/60 CE,VDEGS Without plug and supply cord Yes - all 850 mm 600 mm 600 mm 960 mm 676 mm 719 mm 44,0 Kg 49,0 Kg	
50/60 CE,VDEGS Without plug and supply cord Yes - all 850 mm 600 mm 600 mm 960 mm 676 mm 719 mm 44,0 Kg 49,0 Kg	•
CE,VDEGS Without plug and supply cord Yes - all 850 mm 600 mm 960 mm 960 mm 676 mm 719 mm 44,0 Kg 49,0 Kg	
Without plug and supply cord Yes - all 850 mm 600 mm 600 mm 960 mm 676 mm 719 mm 44,0 Kg 49,0 Kg	
Yes - all 850 mm 600 mm 600 mm 960 mm 676 mm 719 mm 44,0 Kg 49,0 Kg	
850 mm 600 mm 600 mm 960 mm 676 mm 719 mm 44,0 Kg 49,0 Kg	
600 mm 960 mm 676 mm 719 mm 44,0 Kg 49,0 Kg	
960 mm 676 mm 719 mm 44,0 Kg 49,0 Kg	600 mm
676 mm 719 mm 44,0 Kg 49,0 Kg	600 mm
719 mm 44,0 Kg 49,0 Kg	960 mm
44,0 Kg 49,0 Kg	676 mm
49,0 Kg	719 mm
49,0 Kg	44,0 Kg
31661	Steel

/ Electric cooker; Energy efficiency class: A Painted Wire type 1x 1 Mechanical Mechanical No delay option 2 729336

Automatic programmes	
Integrated cleaning system	
Location of 1st heating element	
Type of 1st heating element	
Dimension of 1st heating element	
Power of 1st heating element	
Location of 2nd heating element	
Type of 2nd heating element	
Dimension of 2nd heating element	
Power of 2nd heating element	
Location of 3rd heating element	
Type of 3rd heating element	
Dimension of 3rd heating element	
Power of 3rd heating element	
Location of 4th heating element	
Type of 4th heating element	
Dimension of 4th heating element	
Power of 4th heating element	
Power ON indicator	
Plate ON indicator	
Type of lid	
Residual heat indicator	
Main on/off switch	
Safety device	
Control panel information	
Cavity material	
Oven lighting	
Position of interior lights	
Grill motor with rotisserie set	
Meat probe	
Storage compartment	
Additional equipment included	

Energy label information / Performance :

Energy efficiency class - NEW (2010/30/EC)	Α
Standard load cooking time - fan cooking	49,3 min
Standard load cooking time - conventional cooking	51,5 min
Surface of the largest baking pan	1316 cm2
Energy consumption per cycle conventional (2010/30/ES)	0,92
Energy consumption gas oven per cycle conventional (2010/30/ES)	1
Energy consumption per cycle forced air convection (2010/30/ES)	0,87
Usable volume of cavity (2010/30/ES)	65
Number of cavities - NEW (2010/30/EC)	1
Energy consumption forced air convection	0,00
Energy efficiency index (2010/30/EC)	106,1
Noise	46 db(A) re 1pW
Product size	Large

2/2

Easy to clean enamel
Front left
Standard hotplate with temperature limiter
220 mm
2000/0 W
Rear left
Rapid hotplate
145 mm
1500/0 W
Rear right
Rapid hotplate
180 mm
2000/0 W
Front right
Standard hotplate
80 mm
450/0 W
Yes
1
None
Without
No
Thermo electric oven protection
1
1
Yes
Rear
No
1
Pull-out drawer
Deep baking pan - 2
Oven grid - 1